

University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8113

To: Mr. Wang Bo (Project Manager)

Dr. Umbreen

China Electric Power Equipment and Technology Co. Ltd Project:±660KV Matiari-Lahore HVDC Transmission, (Lot 7 & 8, Tower No. G-2029)

Our Ref. No. CL/CED/ 7433 Dated: 05-03-19

Your Ref. No. CET/PAK/HVDC/UET-19-005 Dated: 12-02-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 18-02-19 Tested on: 25-02-19 in dry/wet condition

ir —		I				1		1		
		Ca	sting	Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*	///	∕et W	/eight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
		(gms)		ıs)			(Sq. in)	(Tons/lbs)	(Psi)	
1	Leg A	15	1	2019	6Diax12	13.6	28.28	55	4360	Non Engraved
2	Leg A	15	1	2019	6Diax12	14	28.28	65	5150	Non Engraved
3	Leg A	15	1	2019	6Diax12	14	28.28	65	5150	Non Engraved
4	Leg C	15	1	2019	6Diax12	13.6	28.28	59	4680	Non Engraved
5	Leg C	15	1	2019	6Diax12	13.6	28.28	59	4680	Non Engraved
6	Leg C	15	1	2019	6Diax12	13.6	28.28	69	5470	Non Engraved
End										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6">http://www.uet.edu.pk/faculties/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6</a>

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8113

To: Mr. Wang Bo (Project Manager)

Dr. Aqsa

China Electric Power Equipment and Technology Co. Ltd Project:±660KV Matiari-Lahore HVDC Transmission Line, (Lot 7 & 8, Tower No. G-2027)

Our Ref. No. CL/CED/ 7434 Dated: 05-03-19

Your Ref. No. CET/PAK/HVDC/UET-19-006 Dated: 14-02-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 18-02-19 Tested on: 28-02-19 in dry/wet condition

		Са	sting	Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*	Μ	/et W	/eight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
		(gms)		ıs)			(Sq. in)	(Tons/lbs)	(Psi)	
1	Leg A	24	24 1 2019		6Diax12	13.6	28.28	73	5790	Engraved
2	Leg A	24	1	2019	6Diax12	13.6	28.28	67	5310	Engraved
3	Leg A	24	1	2019	6Diax12	13.6	28.28	63	5000	Engraved
4	Leg C	24	1	2019	6Diax12	13.4	28.28	67	5310	Non Engraved
5	Leg C	24	1	2019	6Diax12	13.4	28.28	67	5310	Non Engraved
6	Leg C	24 1 2019		2019	6Diax12	13.4	28.28	48	3810	Non Engraved
End										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6">http://www.uet.edu.pk/faculties/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6</a>

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8113

To: Mr. Wang Bo (Project Manager)

Dr. Aqsa

China Electric Power Equipment and Technology Co. Ltd Project:±660KV Matiari-Lahore HVDC Transmission Line, (Lot 7 & 8, Tower No. G-2030)

Our Ref. No. CL/CED/ 7435 Dated: 05-03-19

Your Ref. No. CET/PAK/HVDC/UET-19-007 Dated: 17-02-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

28-02-

Specimens received on: 18-02-19 Tested on: 19 in dry/wet condition

		Ca	sting	Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*	//\	/et W	/eight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
		(gms)						(Tons/lbs)	(Psi)	
1	Leg A	20	1	2019	6Diax12	13.4	28.28	65	5150	Non Engraved
2	Leg A	20	1	2019	6Diax12	13.8	28.28	47	3730	Non Engraved
3	Leg A	20	1	2019	6Diax12	13.4	28.28	55	4360	Non Engraved
4	Leg C	20	1	2019	6Diax12	13.7	28.28	59	4680	Non Engraved
5	Leg C	20	1	2019	6Diax12	13.6	28.28	61	4840	Non Engraved
6	Leg C	20	1	2019	6Diax12	13.6	28.28	67	5310	Non Engraved
End										
8										
9										
10										
11										
12										
13								_		
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing">http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing</a> reports&id=6

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8113

To: Mr. Wang Bo (Project Manager)

Dr. Aqsa

China Electric Power Equipment and Technology Co. Ltd Project:±660KV Matiari-Lahore HVDC Transmission Line, (Lot 7 & 8, Tower No. G-2029)

Our Ref. No. CL/CED/ 7436 Dated: 05-03-19

Your Ref. No. CET/PAK/HVDC/UET-19-008 Dated: 19-02-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 18-02-19 Tested on: 28-02-19 in dry/wet condition

		Са	sting	Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*		_	/eight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
		(gms)		ns)			(Sq. in)	(Tons/lbs)	(Psi)	
1	Leg B	22	22 1 2019		6Diax12	13.6	28.28	75	5950	Engraved
2	Leg B	22	1	2019	6Diax12	13.6	28.28	94	7450	Engraved
3	Leg B	22	1	2019	6Diax12	13.4	28.28	75	5950	Non Engraved
4	Leg D	22	1	2019	6Diax12	13.6	28.28	81	6420	Non Engraved
5	Leg D	22	1	2019	6Diax12	13.4	28.28	54	4280	Non Engraved
6	Leg D	22	1	2019	6Diax12	13.4	28.28	75	5950	Non Engraved
End										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6">http://www.uet.edu.pk/faculties/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6</a>

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8113

To: Mr. Wang Bo (Project Manager)

Dr. Aqsa

China Electric Power Equipment and Technology Co. Ltd Project:±660KV Matiari-Lahore HVDC Transmission Line, (Lot 7 & 8, Tower No. G-2027)

Our Ref. No. CL/CED/ 7437 Dated: 05-03-19

Your Ref. No. CET/PAK/HVDC/UET-19-009 Dated: 21-02-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 18-02-19 Tested on: 28-02-19 in dry/wet condition

		Ca	sting	Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*	///	/et W	/eight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
			(gm	ıs)			(Sq. in)	(Tons/lbs)	(Psi)	
1	Leg B	24	24 1 2019		6Diax12	13.2	28.28	86	6820	Engraved
2	Leg B	24	1	2019	6Diax12	13.2	28.28	85	6740	Engraved
3	Leg B	24	1	2019	6Diax12	13.6	28.28	71	5630	Engraved
4	Leg D	24	1	2019	6Diax12	13.6	28.28	61	4840	Non Engraved
5	Leg D	24	1	2019	6Diax12	13.4	28.28	61	4840	Non Engraved
6	Leg D	24	1	2019	6Diax12	13.2	28.28	55	4360	Non Engraved
End										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6">http://www.uet.edu.pk/faculties/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6</a>

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8113

To: Mr. Wang Bo (Project Manager)

Dr. Aqsa

China Electric Power Equipment and Technology Co. Ltd Project:±660KV Matiari-Lahore HVDC Transmission Line, (Lot 7 & 8, Tower No. G-2368)

Our Ref. No. CL/CED/ 7438 Dated: 05-03-19

Your Ref. No. CET/PAK/HVDC/UET-19-001 Dated: 21-02-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 18-02-19 Tested on: 28-02-19 in dry/wet condition

						1				
		Ca	sting	Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*	/Wet Weight			(in)	(lbs./gms)	X- Section	load	Stress	Remarks
		(gms)		ıs)			(Sq. in)	(Tons/lbs)	(Psi)	
1	Leg B	20	1	2019	6Diax12	13	28.28	53	4200	Engraved
2	Leg B	20	1	2019	6Diax12	13	28.28	65	5150	Engraved
3	Leg B	20	1	2019	6Diax12	13.2	28.28	61	4840	Engraved
End										
5										
6										
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6">http://www.uet.edu.pk/faculties/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6</a>

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8196

To: Arsalan Arshad (Project Manager)

Engr.Abdul Rehman

**DEPAC**, Lahore

Project:Construction of Dr. Maqbool Ahmad Block, King Edward Medical University (KEMU), Lahore

Our Ref. No. CL/CED/ 7439 Dated: 05-03-19

Your Ref. No. T/12/03/18 Dated: 28-02-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 04-03-19 Tested on: 05-03-19 in dry/wet condition

				<b></b>	0:					
		Cas	sting	Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*	/W	et W	/eight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
		(gms)					(Sq. in)	(Tons/lbs)	(Psi)	
1	Retaining Wall	29	1	2019	6Diax12	13.6	28.28	61	4840	Non Engraved
2	Retaining Wall	29	1	2019	6Diax12	13.4	28.28	67	5310	Non Engraved
3	Retaining Wall	29	1	2019	6Diax12	13.6	28.28	59	4680	Non Engraved
End										
5										
6										
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6">http://www.uet.edu.pk/faculties/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6</a>

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

8190

Го: Engr. Khalid Noor (C.E.O Astaco)

Engr.Abdul Rehman

Astaco Engineers and Contractors, Lahore Project:

Our Ref. No. CL/CED/

7440

Nil

Dated:

05-03-19

Your Ref. No.

Dated:

04-03-19

#### **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on: 04-03-19 Tested on: 05-03-19 in dry/wet condition

		Casting Date*			Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*			/eight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
		(gms)				(Sq. in)	(Tons/lbs)	(Psi)		
1	Slab	17	2	2019	6x6x6	8.2	36	75	4670	Non Engraved
2	Slab	17	2	2019	6x6x6	8.2	36	84	5230	Non Engraved
3	Slab	17	2	2019	6x6x6	8.2	36	69	4300	Non Engraved
End										
5										
6										
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website <a href="http://www.uet.edu.pk/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6">http://www.uet.edu.pk/faculties/faculties/faculties/facultiesinfo/department?RID=testing\_reports&id=6</a>

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

<sup>\*</sup> as engraved on the specimens (if any)

<sup>\*\*</sup> BS3921 requires average of ten clay brick samples for crushing strength and water absorption

<sup>\*\*\*</sup> BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

<sup>\*\*\*\*</sup> ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprerssive strength