

Plain and Reinforced Concrete Laboratory Department of Civil Engineering

University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

> 10244 Dr.Mazhar Saleem

To: Nasir Mahmood Khan (Partner)

N.A. Associates, Lahore

Project: Construction of Commercial Building at Plot N.44-D-1, Gulberg-III, Lahore

| Our Ref. No. CL/CED/ | 344 | Dated: | 03-07-20 |
|----------------------|--------------------|--------|----------|
| Your Ref. No. | NAA/Bill/44-D-I/25 | Dated: | 01-07-20 |

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on:

01-07-20 Tested on:

02-07-20 in dry/wet condition

| | | Cas | sting | Date* | Size | Weight | Area of | Ultimate | Ultimate | |
|---------|---------------------------|-----|-------|--------|---------|------------|---------------|------------|----------|--------------|
| Sr. No. | Mark* | ſW | et V | Veight | (in) | (lbs./gms) | X- Section | load | Stress | Remarks |
| | | | (gn | ıs) | | | (Sq. in) | (Tons/lbs) | (Psi) | |
| 1 | Retaining Wall Part- 2 | 23 | 6 | 2020 | 6Diax12 | 13.6 | 28.28 | 41 | 3250 | Non Engraved |
| 2 | Retaining Wall Part- 2 | 23 | 6 | 2020 | 6Diax12 | 13.6 | 28.28 | 35 | 2780 | Non Engraved |
| 3 | Retaining Wall Part- 2 | 23 | 6 | 2020 | 6Diax12 | 14 | 28.28 | 49 | 3890 | Non Engraved |
| 4 | | | | | | | | | | |
| 5 | | | | | | | | | | |
| 6 | | | | | | | | | | |
| 7 | | | | | | | | | | |
| 8 | | | | | | | | | | |
| 9 | | | | | | | | | | |
| 10 | | | | | | | | | | |
| 11 | | | | | | | | | | |
| 12 | | | | | | | | | | |
| 13 | | | | | | | | | | |
| 14 | | | | | | | | | | |
| 15 | | | | | | | | | | |
| 16 | | | | | | | | | | |

Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing_reports&id=6

* as engraved on the specimens (if any)

** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

**** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)



Plain and Reinforced Concrete Laboratory Department of Civil Engineering

University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

To: Nasir Mahmood Khan (Partner)

10244 Dr Mazhar Saleem

N.A. Associates, Lahore

Project: Construction of Commercial Building at Plot N.44-D-1, Gulberg-III, Lahore

| Our Ref. No. CL/CED/ | 345 | Dated: | 03-07-20 |
|----------------------|--------------------|--------|----------|
| Your Ref. No. | NAA/Bill/44-D-I/26 | Dated: | 01-07-20 |

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on:

01-07-20 Tested on:

02-07-20 in dry/wet condition

| _ | | Cas | sting | JDate* | Size | Weight | Area of | Ultimate | Ultimate | |
|---------|--------------------------|-----|-------|--------|---------|------------|---------------|------------|----------|--------------|
| Sr. No. | Mark* | w | 'et V | Veight | (in) | (lbs./gms) | X- Section | load | Stress | Remarks |
| | | | (gn | ıs) | | | (Sq. in) | (Tons/lbs) | (Psi) | |
| 1 | R.C.C. Column Part- 2 | 20 | 6 | 2020 | 6Diax12 | 13 | 28.28 | 23 | 1830 | Non Engraved |
| 2 | R.C.C. Column Part- 2 | 20 | 6 | 2020 | 6Diax12 | 14 | 28.28 | 55 | 4360 | Non Engraved |
| 3 | R.C.C. Column Part- 2 | 20 | 6 | 2020 | 6Diax12 | 14 | 28.28 | 33 | 2620 | Non Engraved |
| 4 | | | | | | | | | | |
| 5 | | | | | | | | | | |
| 6 | | | | | | | | | | |
| 7 | | | | | | | | | | |
| 8 | | | | | | | | | | |
| 9 | | | | | | | | | | |
| 10 | | | | | | | | | | |
| 11 | | | | | | | | | | |
| 12 | | | | | | | | | | |
| 13 | | | | | | | | | | |
| 14 | | | | | | | | | | |
| 15 | | | | | | | | | | |
| 16 | | | | | | | | | | |

Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing reports&id=6

* as engraved on the specimens (if any)

** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength **** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)



To: Muhammad Azeem (Operation Manager)

Project: Hotel Building at 24-A Block E/2 at Gulberg III, Lahore

346

AAA/24A/0015

Amer Adnan Associates, Lahore

Our Ref. No. CL/CED/

Your Ref. No.

Plain and Reinforced Concrete Laboratory Department of Civil Engineering

University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

03-07-20

02-07-20

10245

Dr Mazhar Saleem

COMPRESSION TEST REPORT Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers 02-07-20 Tested on: 02-07-20 Specimens received on: in dry/wet condition Casting Date* Size Weight Area of Ultimate Ultimate Š Mark* /Wet Weight (in) (lbs./gms) X-Section load Stress Remarks ັດ (Tons/lbs) (gms) (Sq. in) (Psi) 1 3 6 2020 6Diax12 14.2 28.28 69 5470 Non Engraved 2 3 6 2020 6Diax12 14.2 28.28 5470 Non Engraved 69 3 3 6 2020 6Diax12 14 28.28 67 5310 Non Engraved 4 24 6 2020 6Diax12 14.6 28.28 55 4360 Non Engraved 24 6 2020 6Diax12 5 14.2 28.28 53 4200 Non Engraved 24 6 2020 6Diax12 14 28.28 57 4520 6 Non Engraved 7 8 9 10 11 12 13 14 15 16 Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing_reports&id=6

Dated:

Dated:

* as engraved on the specimens (if any)

** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

**** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)



Plain and Reinforced Concrete Laboratory Department of Civil Engineering

University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

To: Municipal Officer (I&S)

10241 Dr. Umbreen

Municipal Corporation, Sialkot

Project: Rehabilitation/Construction of R.C.C Sewer Line and Tuff Tiles Street Mubarik From Main Road Zafawal Road Towards Mubarik House U/C Pindi Arayan Tehsil & District Sialkot

| Our Ref. No. CL/CED/ | 347 | Dated: | 03-07-20 |
|----------------------|-------------|--------|----------|
| Your Ref. No. | MCS/I&S/213 | Dated: | 15-03-20 |

COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on:

30-06-20 Tested on:

01-07-20 in dry/wet condition

| ö | | Casting Date* | Size | Weight | Area of | Ultimate | Ultimate | |
|-------|----------------|------------------|-----------|------------|---------------|------------|----------|---------|
| Sr. N | Mark* | /Wet Weight | (in) | (lbs./gms) | X- Section | load | Stress | Remarks |
| | | (gms) | | | (Sq. in) | (Tons/lbs) | (Psi) | |
| 1 | Uni-block Grey | | 2.4 Thick | 3523 | 37.25 | 150 | 9020 | |
| 2 | Uni-block Grey | | 2.4 Thick | 3426 | 37.25 | 160 | 9630 | |
| 3 | Uni-block Grey | | 2.4 Thick | 3388 | 37.25 | 160 | 9630 | |
| 4 | Uni-block Red | | 2.4 Thick | 3336 | 37.25 | 150 | 9020 | |
| 5 | Uni-block Red | | 2.4 Thick | 3376 | 37.25 | 158 | 9510 | |
| 6 | | | | | | | | |
| 7 | | | | | | | | |
| 8 | | | | | | | | |
| 9 | | | | | | | | |
| 10 | | | | | | | | |
| 11 | | | | | | | | |
| 12 | | | | | | | | |
| 13 | | | | | | | | |
| 14 | | | | | | | | |
| 15 | | | | | | | | |
| 16 | | | | | | | | |

Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing_reports&id=6

* as engraved on the specimens (if any)

** BS3921 requires average of ten clay brick samples for crushing strength and water absorption

*** BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

**** ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)