

University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

### To: Ali Anwar Malik Lahore **Project: Nil**

Our Ref. No. CL/CED/ 1080-1 of 2 Dated: 26-10-20 Dated: Your Ref. No. Nil 20-10-20

## COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

20-10-20 Specimens received on:

Tested on:

21-10-20 in dry/wet condition

-			Casting Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No	Mark*	/Wet Weight	(in)	(lbs./gms)	X-Section	load	Stress	Remarks	
		(gms)			(Sq. in)	(Tons/lbs)	(Psi)		
1	Solid Block		11.9x5.9x8.0	19	70.21	72	2300		
2	Solid Block		11.9x5.8x8.0	21	69.02	85	2760		
3									
4									
5									
6									
7									
8									
9									
10									
11									
12									
13									
14									
15									
16									

Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing\_reports&id=6

\* as engraved on the specimens (if any)

\*\* BS3921 requires average of ten clay brick samples for crushing strength and water absorption

\*\*\* BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

\*\*\*\* ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)

### Director/Dy. Director Concrete Laboratory

24 Dr. Aqsa



Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing\_reports&id=6

\* as engraved on the specimens (if any)

\*\* BS3921 requires average of ten clay brick samples for crushing strength and water absorption

\*\*\* BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

\*\*\*\* ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

#### To: Assistant Executive Engineer **KBCMA**, **CVAS**, Narowal

Project: Construction of Boys Hostel at CVAS, Narowal

Our Ref. No. CL/CED/	1082	Dated:	26-10-20
Your Ref. No.	AEE/NC/017	Dated:	05-10-20

## COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on:

12-10-20 Tested on:

26-10-20 in dry/wet condition

10681

Dr.Mazhar Saleem

No.	Mark*	Casting Date* /Wet	Size	Weight	Area of	Ultimate	Ultimate	Remarks
Sr.	Mark	Weight	(11)	(103./9113)	X-0001011		01033	Remarks
		(gms)			(Sq. in)	(Tons/lbs)	(Psi)	
1	HB		8.9x4.4x2.9	3119	39.16	33	1890	
2	HB		9.0x4.3x2.9	3170	38.7	33	1910	
3	HB		8.8x4.3x2.8	3187	37.84	49	2910	
4	HB		8.9x4.4x2.9	3240	39.16	45	2580	
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								

Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing\_reports&id=6

\* as engraved on the specimens (if any)

\*\* BS3921 requires average of ten clay brick samples for crushing strength and water absorption

\*\*\* BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

\*\*\*\* ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as comprensive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

#### To: Rashid Kamran (Resident Engineer) CM Div., Nespak (Pvt.) Ltd. Lahore

Dr.Mazhar Saleem

9

Project: Rehabilitation & Improvement of Roads Infrastructure in Allama Iqbal Town, Lahore

Our Ref. No. CL/CED	/ 1083	Dated:	26-10-20	
Your Ref. No.	4047-R3/13/RK/1A/0109	Dated:	28-05-20	

## **COMPRESSION TEST REPORT**

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on:

16-10-20 Tested on:

26-10-20 in dry/wet condition

r										
		Cas	sting	J Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No	Mark*	/Wet Weight		(in)	(lbs./gms)	X- Section	load	Stress	Remarks	
			(gn	ıs)			(Sq. in)	(Tons/lbs)	(Psi)	
1		25	2	2020	6Diax12	13.8	28.28	69	5470	Non Engraved
2		25	2	2020	6Diax12	14	28.28	83	6580	Non Engraved
3		25	2	2020	6Diax12	13.8	28.28	67	5310	Non Engraved
4		25	2	2020	6Diax12	14	28.28	79	6260	Non Engraved
5		25	2	2020	6Diax12	14	28.28	83	6580	Non Engraved
6		25	2	2020	6Diax12	14	28.28	83	6580	Non Engraved
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing\_reports&id=6

\* as engraved on the specimens (if any)

\*\* BS3921 requires average of ten clay brick samples for crushing strength and water absorption

\*\*\* BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

\*\*\*\* ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)



University of Engineering and Technology, Lahore Phone Nos. 042-99029202, 042-99029217

#### To: Rashid Kamran (Resident Engineer)

Dr.Mazhar Saleem

9

CM Div., Nespak (Pvt.) Ltd. Lahore

Project: Construction of Pedestrian Overhead Bridge at Shabbir Usmani Road Infront of Jinah Hospital, Lahore

Our Ref. No. CL/CI	ED/	1084	Dated:	26-10-20
Your Ref. No.	4047-R/13/	/RK/07/AFE/373	Dated:	24-06-20

## COMPRESSION TEST REPORT

Concrete Cubes/Concrete Cylinders/Bricks/Cores/Tuff Tiles/Pavers

Specimens received on:

16-10-20 Tested on:

26-10-20 in dry/wet condition

		Cas	sting	g Date*	Size	Weight	Area of	Ultimate	Ultimate	
Sr. No.	Mark*	w	et V	Veight	(in)	(lbs./gms)	X- Section	load	Stress	Remarks
			(gms)				(Sq. in)	(Tons/lbs)	(Psi)	
1		18	2	2020	6Diax12	14.2	28.28	77	6100	Non Engraved
2		18	2	2020	6Diax12	14	28.28	79	6260	Non Engraved
3		18	2	2020	6Diax12	14	28.28	63	4990	Non Engraved
4										
5										
6										
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										

Results can also be seen on website http://www.uet.edu.pk/faculties/facultiesinfo/department?RID=testing\_reports&id=6

\* as engraved on the specimens (if any)

\*\* BS3921 requires average of ten clay brick samples for crushing strength and water absorption

\*\*\* BS5328 requires mean of two cube sample strength at 28 days as characteristic strength

\*\*\*\* ACI318-08 requires mean of two sample (6"diax12" cylinder) strength at 28 days as compressive strength

Note: Above results pertain to the unsealed samples supplied to the laboratory

The laboratory is not responsible for sampling, originality and construction conditions (such as mix proportion, w/c ratio, compaction, curing and quality of ingredients). The test results are recommended to be interpreted in the light of above factors by the engineer.

supervisor(lab)